## EVAPCO, INC. UNIT DWG. # SERIAL # MODEL # **CLOSED CIRCUIT COOLER** NTS W2091412-ERE-RS ATC-1006E 5/5/2024 NOTES: 1. (M)- FAN MOTOR LOCATION (M)**BOTTOM OUTLET** 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD 18 1/8 65 7/8 FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 4. + UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE SEPARATE DRAWINGS FOR ACCESSORIES) 5. 3/4" DIA. MOUNTING HOLES. REFER TO 8'-5 1/2" RECOMMENDED STEEL SUPPORT 6. THE SPRAY PUMP SHOULD BE SIZED FOR 600 GPM AND 2.5 PSIG AT THE INLET CONNECTION FACE 2 7. \*- APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING **PIPING** 13' 11 3/4" FACE 1 **PLAN VIEW** 19 3/4 + ACCESS DOOR 26 3/8 13/8 -**-** 48 3/4 → 105 3/8 11 1/8 6 FPT (2) 4 BFW <del>Ó</del>— FLUID IN (2) 1/2 FPT VENTS **INLET** 13'-5 1/2" (2) 4 BFW FLUID OUT -5 1/8 56 1/8 8'-5 1/2" -13' 11 3/4" FACE 2 FACE 1 NO. OF SHIPPING SECTIONS SHIPPING OPERATING HEAVIEST SECTION lbs.+ 17940 24750 lbs. 15910 lbs 2 WEIGHT WEIGHT WEIGHT