NOTES: 1. (M)- FAN MOTOR LOCATION 2. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END 3. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 4. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING 5. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT IN [METRIC] [mm]	INIT CLOSED CIRCUIT COOLER			EVADOO TNO EVGIDEO					DWG. # WLETM1806-DRD-SF			REV.
1. (M. FAN MOTOR LOCATION EW PLAN MOTOR LOCATION BRY DENOTES BRY LED FOR WELDING BRY DENOTES BRY LED FOR WELDING BRY DENOTES BRY LED FOR WELDING BRY DENOTES RANCE PLAN MOTOR LOCATION BRY DENOTES BRY LED FOR WELDING BRY DENOTES RANCE PLAN WELDING A COESSORIES (SEE ACCESSORY DRAWINGS) A COESSORIES (SEE ACCESSORY DRAWINGS) A WITHOUGH DURING DURINGS ON DO NOT LICE FOR PRE-FARMINGS NOS DO NOT LICE FOR	ODEL #	LSWE 10-3L18-Z	SCALE NTS		VAPCO,	TIA	C.		SERIAI	L #		DATE 5/19/2024
2'-6 3/8" * FACE A SERIES FLOW PIPING (BY OTHERS) 1'-10 1/4" * C100 BFW FLUID IN (4) 4" [100]	1. (M)- F 2. MPT I FPT I BFW GVD FLG I PE DI 3. +UNI ACCE 4. 3/4" [RECC 5. DIME 6. * - AP USE I 7. HEAV 8. MAKE 20 ps 9. SERII	AN MOTOR LOCATION DENOTES MALE PIPE THRE DENOTES FEMALE PIPE THE DENOTES BEVELED FOR VENTER OF THE DENOTES BEVELED FOR VENTER OF THE DENOTES FLANGE OF THE DENOTES PLAIN END FOR PRESENTED AS FOLLOW PROXIMATE DIMENSIONS FOR PRE-FABRICATION OF THE DENOTES OF THE DENOTED FOR PRE-FABRICATION OF THE D	IREAD VELDING UDE RY DRAWINGS) LES. REFER TO RT DRAWING WS: ENGLISH FT IN [METRIC] [mm] DO NOT CONNECTING PIPIN	NG					FACE C			FACE D
4 3/4" * (2) ACCESS DOOR 3" [80] FPT OVERFLOW 2'-7 1/2" [2004] 2'-7 3/4" [806] 3'' [80] MPT [613] 2'-7 1/4" [806] 3'' [80] MPT [635] 4'-1 7/8" [3493] FACE A	1'-10 1	SERIES FLOW PIPING (BY OTHERS)		[14	(4) 4" [100] BFW FLUID IN	1 1/8"		(4) 1/2" [15] FPT VENT				
2'-7 3/4" [806] 3'-7 1/4" [1099] 4'-1 7/8" [1267]		(2) ACCESS DOOR 3" [80] FPT OVERFLOW			2" [50] MPT 8'-	12'-7	5/8"	DRAIN (BY OTHERS)				
FACE B SHIPPING 18720 lbs+ [8495] kg+ OPERATING WEIGHT 28470 lbs+ [12915] kg+ HEAVIEST SECTION 11530 lbs+ [5230] kg+ NO. OF SHIPPING SECTIONS 2 DRAWN BY: TLS		3'-7 1/4" [1099]	9	DRAIN '-9 3/4" 2991]		<u>, , , , , , , , , , , , , , , , , , , </u>	2'-1" [635]	•	18'-1/4" [5493]			