

NOTES:
 1. (M)- FAN MOTOR LOCATION
 2. HEAVIEST SECTION IS UPPER SECTION
 3. MPT DENOTES MALE PIPE THREAD
 FPT DENOTES FEMALE PIPE THREAD
 BFW DENOTES BEVELED FOR WELDING
 GVD DENOTES GROOVED
 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS)
 5. MAKE-UP WATER PRESSURE
 20 psi MIN [137 kPa], 50 psi MAX [344 kPa]
 6. 3/4" DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING.
 7. *- APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTION PIPING.
 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH IN [METRIC] [mm]

FACE 2 PLAN VIEW

(4) 4 [100] BFW REFRIG IN
 (4) 1/2 [15] BFW PURGE
 9 1/2 * [241]
 4 1/8 [105]
 53 3/4 * [1365]
 18 3/8 * [466]
 18'-2 5/8" [5553]
 (4) 4 [100] BFW REFRIG OUT
 INTERIOR PAN CONNECTIONS THIS SIDE

FACE 1 (Top Elevation)

INTERIOR PAN CONNECTIONS THIS SIDE
 11'-11" [3632]
 4 [102]
 24'-2" [7366]
 11'-11" [3632]

FACE 1 (Front Elevation)

ACCESS DOOR
 TYP BOTH SIDES
 24'-0" [7315]
 122 1/8 [3102]
 96 1/2 [2451]

SHIPPING WEIGHT	63400 lbs+ [28760] kg+	OPERATING WEIGHT	94060 lbs+ [42665] kg+	HEAVIEST SECTION WEIGHT	21950 lbs+ [9960] kg+	NO. OF SHIPPING SECTIONS	4	DRAWN BY:	TLS
-----------------	------------------------	------------------	------------------------	-------------------------	-----------------------	--------------------------	---	-----------	-----