

NOTES:

1. (M) - FAN MOTOR LOCATION
2. HEAVIEST SECTION IS UPPER SECTION
3. MPT DENOTES MALE PIPE THREAD
FPT DENOTES FEMALE PIPE THREAD
BFW DENOTES BEVELED FOR WELDING
4. + UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE SEPARATE DRAWINGS FOR ACCESSORIES)
5. 19mm DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING
6. MAKE-UP WATER PRESSURE-137 kPa MIN, 344 kPa MAX
7. * - APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING.

The drawing consists of three main views: a front view (FACE 1) at the bottom left, a plan view at the bottom right, and a side view (FACE 1) at the top right. The front view shows two identical vertical sections side-by-side. Each section has a top cylindrical part with a 34mm diameter, a middle section with two (8) 4 BFW fluid in/out ports and (4) 100 BFW ports, and a bottom section with a (2) 50 MPT make-up port, a (2) 80 MPT drain port, and a (2) 80 MPT overflow port. The plan view shows the top of the unit with two access doors and an (8) 15 FPT vent. The side view shows the unit's profile with a total height of 7344mm and a width of 5486mm. Dimensions are provided in millimeters, and weights are in kilograms.

SHIPPING WEIGHT	23140	kg	+	OPERATING WEIGHT	36450	kg	HEAVIEST SECTION WEIGHT	9780	kg	NO. OF SHIPPING SECTIONS	4
-----------------	-------	----	---	------------------	-------	----	-------------------------	------	----	--------------------------	---