EVAPCO, INC. UNIT MODEL # DATE SERIAL # **CLOSED CIRCUIT COOLER** NTS W2123606-ERC-LFHR PMC-962E 4/20/2024 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HÉAVIEST SECTION IS UPPER SECTION (2) 3. MPT DENOTES MALE PIPE THREAD **BOTTOM OUTLET** FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING (M) (M) 24 1/8 4. + UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE SEPARATE DRAWINGS FOR ACCESSORIES) 5. 3/4" DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT 11'-10" 6. THE SPRAY PUMP SHOULD BE SIZED FOR 2400 GPM AND 2.5 PSIG AT THE INLET CONNECTION FACE 1 7. *- APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING **PIPING** 36'-2 1/2" FACE 2 **PLAN VIEW** 22 1/4 19 3/4 -**-** 19 3/4 ACCESS ACCESS 34 1/4 34 1/4 1 5/8 -DOOR DOOR **-**1 5/8 105 5/8 6 FPT -6 FPT (4) 1/2 FPT (4) 1/2 FPT (8) 4 BFW FLUID IN **INLET** INLET 10 3/8 — 22 1/4 **VENT VENT** 15'-11 3/4" FLUID OUT - 5 1/4 86 1/8 36'-2 1/2" - 11'-10" -FACE 1 FACE 2 NO. OF SHIPPING SECTIONS SHIPPING OPERATING HEAVIEST SECTION 43080 lbs. 57900 lbs. 17610 lbs. 4 WEIGHT WEIGHT WEIGHT