EVAPCO, INC. UNIT MODEL # DATE SERIAL # CQTM2408-DRA-ST N.T.S. **EVAPORATIVE CONDENSER PMCQ-820** 4/26/2024 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HÉAVIEST SECTION IS LOWER SECTION 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. 3/4" DIA. MOUNTING HOLES. REFER TO 9'-9 3/4" RECOMMENDED STEEL SUPPORT DRAWING. [2991] 6. MAKE-UP WATER PRESSURE FACE 1 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] **PLAN VIEW** 7. *-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH IN [METRIC] [mm] 24'-7/8" [7338] FACE 2 30 3/8* [772] _ 57* [1448] (4) 4[100] BFW -30 3/4* REFRIG IN [781] (4) 4[100] BFW -**REFRIG OUT** 69 1/2 [1766] 2[50] MPT MAKE UP **OVERSIZED** 14'-3 7/8" **ACCESS DOORS** [4366] 119* [3023] 102 3/8 3[80] MPT [2600] **DRAIN** 5 3/8 29 [737] 24'-7/8" [7338] 18 [457] 16 3/8 [416] 137 (2) 3[80] FPT 50 3/8 20 [507] [1280] **OVERFLOW** 44 3/4 1137] 9'-9 3/4" 2991 FACE 2 FACE 1 SHIPPING OPERATING NO. OF SHIPPING SECTIONS HEAVIEST SECTION 31710 lbs+ [14383] kg+ 40390 lbs+ [18321] kg+ 10990 lbs+ [4985] kg+ 3 WEIGHT WEIGHT WEIGHT