EVAPCO, INC. UNIT DATE MODEL # SCALE SERIAL # **CLOSED CIRCUIT COOLER** NTS W2123610-ERC-SR CATC-504 5/10/2024 NOTES: BOTTOM 1. (M)- FAN MOTOR LOCATION OUTLET 2. HEAVIEST SECTION IS UPPER SECTION 90 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD (M) 24 1/8 (M) BFW DENOTES BEVELED FOR WELDING 4. + UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE SEPARATE DRAWINGS FACE 1 FOR ACCESSORIES) 5. 3/4" DIA. MOUNTING HOLES. REFER TO 11'-10" RECOMMENDED STEEL SUPPORT DRAWING 6. THE SPRAY PUMP SHOULD BE SIZED FOR 2400 GPM AND 2.5 PSIG AT THE INLET CONNECTION 7. *- APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING **PIPING** 8. SERIES FLOW PIPING AND AUX. CROSSOVER DRAIN BY OTHERS 36'-2 1/2" -FACE 2 **PLAN VIEW** 6 FPT — 1 5/8 --15/868 1/2 36 3/4 ACCESS ACCESS 6 FPT DOOR DOOR **INLET** INLET 115 5/8 (4) 4 BFW 10 3/8 **SERIES FLOW** FLUID IN (2) 1/2 FPT (2) 1/2 FPT **PIPING** 39 1/4 (4) 4 BFW **VENT VENT** (SEE NOTE 8) 16'-9 3/4" **FLUID OUT** TYP. AUX. 5 1/4 CROSSOVER 86 1/8 DRAIN (SEE NOTE 8) TYP. 36'-2 1/2" -- 11'-10" FACE 1 FACE 2 NO. OF SHIPPING SECTIONS SHIPPING OPERATING HEAVIEST SECTION 57580 lbs. 77800 24860 4 lbs. lbs WEIGHT WEIGHT WEIGHT