EVAPCO, INC. UNIT MODEL # REV. SERIAL # N.T.S CC2241808-DRC-ST **EVAPORATIVE CONDENSER** CATC-453 5/20/2024 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HÉAVIEST SECTION IS PLENUM/CASING SECTION 3. MPT DENOTES MALE PIPE THREAD ACCESS DOOR ACCESS DOOR FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 6. *-APPROXIMATE DIMENSIONS DO NOT USE 7'-4" [2235] FOR PRE-FABRICATION OF CONNECTING FACE 2 **PLAN VIEW** 7. MAKE-UP IS LOCATED 4 3/4" FROM CONNECTION 18'-0" [5486] FACE 1 21 3/8 ₋ [543] 42 1/4 [1073] 22 7/8 * 581] 55 1/8 [1400] (2) 4 [100] MPT Ö REFRIG IN 27 [686] 44 1/2 12'-8 7/8" [1130] [3883] 5 1/4 * [135] (2) 4 [100] MP7 REFRIG OUT 2 [50] MPT 53 1/4 [1353] 29 5/8 [752] - 2 [50] MPT DRAIN 15 383] 3 [76] 3 7/8 - 3 [80] MPT OVERFLOW 63 5/8 [1614] 26 3/8 18'-0" 7'-4" [2235] [670] [5486] FACE 1 FACE 2 SHIPPING NO. OF SHIPPING SECTIONS OPERATING HEAVIEST SECTION 16360 lbs+ [7420] kg+ 20020 lbs+ [9080] kg+ 13290 lbs+ [6030] kg+ 2 WEIGHT WEIGHT WEIGHT