EVAPCO, INC. UNIT MODEL # REV. SERIAL # N.T.S CC2241810-DRC-ST **EVAPORATIVE CONDENSER** CATC-482 5/20/2024 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HÉAVIEST SECTION IS PLENUM/CASING SECTION 3. MPT DENOTES MALE PIPE THREAD ACCESS DOOR ACCESS DOOR FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 7'-4" [2235] 6. *-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING FACE 2 **PLAN VIEW** 7. MAKE-UP IS LOCATED 4 3/4" FROM CONNECTION 18'-0" [5486] FACE 1 21 3/8 [543] 42 1/4 [1073] 22 7/8 * 581] 55 1/8 [1400] (2) 4 [100] MPT REFRIG IN 34 1/2 * [876] 52 13'-4 3/8" [1321] [4074] (2) 4 [100] MPT REFRIG OUT 2 [50] MPT MAKE-UP 53 1/4 [1353] 29 5/8 [752] - 2 [50] MPT DRAIN 15 383] 3 [76] 3 7/8 [98] 3 [80] MPT OVERFLOW 63 5/8 1614] 26 3/8 18'-0" [670] [5486] FACE 1 FACE 2 SHIPPING NO. OF SHIPPING SECTIONS OPERATING HEAVIEST SECTION 18470 lbs+ [8380] kg+ 22300 lbs+ [10115] kg+ 15400 lbs+ [6985] kg+ 2 WEIGHT WEIGHT WEIGHT