

EVAPCO, INC. UNIT MODEL # REV. SERIAL # N.T.S CC2241812-DRC-ST **EVAPORATIVE CONDENSER** CATC-462 5/20/2024 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HÉAVIEST SECTION IS PLENUM/CASING SECTION 3. MPT DENOTES MALE PIPE THREAD ACCESS DOOR ACCESS DOOR FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 7'-4" 6. *-APPROXIMATE DIMENSIONS DO NOT USE [2235] FACE 2 FOR PRE-FABRICATION OF CONNECTING **PLAN VIEW** 7. MAKE-UP IS LOCATED 4 3/4" FROM CONNECTION 18'-0" [5486] FACE 1 21 3/8 [543] 22 7/8 * [581] 55 1/8 [1400] 42 1/4 1073] O REFRIG IN (2) 4 [100] MPT 42 [1067] 59 1/2 13'-11 7/8" [1511] [4264] 5 1/4 * [135] (2) 4 [100] MPT REFRIG OUT 2 [50] MPT MAKE-UP 53 1/4 [1353] 29 5/8 [752] - 2 [50] MPT DRAIN 15 [383] 3 [76] 3 7/8 3 [80] MPT OVERFLOW 63 5/8 _ 1614 26 3/8 [670] 18'-0" 7'-4" [2235] [5486] FACE 1 FACE 2 SHIPPING OPERATING NO. OF SHIPPING SECTIONS HEAVIEST SECTION 20630 lbs+ [9360] kg+ 24620 lbs+ [11165] kg+ 17560 lbs+ [7965] kg+ 2 WEIGHT WEIGHT WEIGHT