UNIT COOLING TOWER			EV	/ADCO	TNIC EVO	apco	DWG. # TV03061P-DRD-ST	REV.	
MODEL # LPT-3	16L	SCALE NTS	7 EV	APCO,	INC.	2	SERIAL #	DATE 5/9/2024	
NOTES: 1. (M)- FAN MOTOR LOC. 2. MPT DENOTES MALE I FPT DENOTES FEMALI BFW DENOTES BEVEL GVD DENOTES GROO' FLG DENOTES FLANG 3. + UNIT WEIGHT DOE: ACCESSORIES (SEE SI FOR ACCESSORIES) 4. 3/4" DIA. MOUNTING RECOMMENDED STEE DRAWING 5. MAKE-UP WATER PRE: 50 psi MAX 6. DIMENSIONS LISTEL ENGLISH FT-IN [METRIC] MM	PIPE THREAD E PIPE THREAD ED FOR WELDING VED E S NOT INCLUDE EPARATE DRAWINGS HOLES. REFER TO L SUPPORT SSURE-20 psi MIN, D AS FOLLOWS:	S	PLA	FACE B		FACE C		FACE D	
-	1'-8 3/8" [ 517 ]	<b> -</b> -		<u>FACE A</u>					
3'-10 1/4" [ 1176 ]		[100] MPT LET		3"			4'-2" [ 1270 ]	<u> </u>	
<del>,</del> 	3 1/4" TY	P.	6'-	6'-10 1/2" 1 7/8" [ 2096 ] 876 ]	ACCESS DOOR			5'-3 7/8" [1622 ]	
3'-1/4" [ 919 ]	-4" [100] OUTLET	MPT	□		2" [50] MPT — OVERFLOW	2" [50] MPT DRAIN	ACCESS DOOR  1" [25] MPT  MAKE-UP	(†)	
4 3/4" [ 121 ]		4 3/4" 034 ] CE B	2 3/4" [ 70 ]	1'-8 1/8" 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1 3/8" = 1	2'-1/4" [ 616 ] 2'-8 1/4" 5'-6'	"5] 10'-1 7/8" [ 3096 ] FACE A			
SHIPPING WEIGHT	1510 lbs+ [685] kg	g+	OPERATING WEIGHT	2490 lbs+ [1130] kg+	HEAVIEST SECTION WEIGHT	1510 lbs+ [685] kg+	NO. OF SHIPPING SECTIONS	DRAWN BY: JLG	