

EVAPCO, INC. UNIT MODEL # REV. SERIAL # N.T.S CC2241812-DRC-ST **EVAPORATIVE CONDENSER** CATC-504 5/17/2024 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HÉAVIEST SECTION IS PLENUM/CASING SECTION 3. MPT DENOTES MALE PIPE THREAD ACCESS DOOR ACCESS DOOR FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 7'-4" 6. \*-APPROXIMATE DIMENSIONS DO NOT USE [ 2235] FACE 2 FOR PRE-FABRICATION OF CONNECTING **PLAN VIEW** 7. MAKE-UP IS LOCATED 4 3/4" FROM CONNECTION 18'-0" [5486] FACE 1 21 3/8 [ 543 ] 22 7/8 \* [ 581 ] 55 1/8 [ 1400 ] 42 1/4 1073] O REFRIG IN (2) 4 [100] MPT 42 [ 1067] 59 1/2 13'-11 7/8" [ 1511 ] [ 4264 ] 5 1/4 \* [ 135] (2) 4 [100] MPT REFRIG OUT 2 [50] MPT MAKE-UP 53 1/4 [ 1353 ] 29 5/8 [ 752] - 2 [50] MPT DRAIN 15 [ 383] 3 [ 76] 3 7/8 3 [80] MPT OVERFLOW 63 5/8 \_ 1614 26 3/8 [ 670] 18'-0" 7'-4" [ 2235] [5486] FACE 1 FACE 2 SHIPPING OPERATING NO. OF SHIPPING SECTIONS HEAVIEST SECTION 20630 lbs+ [9360] kg+ 24620 lbs+ [11165] kg+ 17560 lbs+ [7965] kg+ 2 WEIGHT WEIGHT WEIGHT