EVAPCO, INC. UNIT MODEL # SERIAL # N.T.S. CQTM3610-DRA-ST **EVAPORATIVE CONDENSER** PMCQ-1212 5/17/2024 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HÉAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 4. +UNIT WEIGHT DOES NOT INCLUDE 9'-9 3/4" ACCESSORIES (SEE ACCESSORY DRAWINGS) [2991] 5. 3/4" DIA. MOUNTING HOLES. REFER TO FACE 1 RECOMMENDED STEEL SUPPORT DRAWING. **PLAN VIEW** 6. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 7. *-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING 36'-2" [11024] **PIPING** 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH IN FACE 2 [METRIC] [mm] 57* 1448] (4) 4[100] BFW REFRIG IN 39 1/4* [997] (4) 4[100] BFW **REFRIG OUT** 78 [1982] 2[50] MPT MAKE UP **OVERSIZED** 15'-3/8" 4582] **ACCESS DOORS** 119* 3[80] MPT 102 3/8 [2600] [3023] DRAIN 5 3/8 137] 29 [737] 20 5/8 [524] 36'-2" [11024] 23 5/8 [600] 50 3/8_ (2) 3[80] FPT 20 [507] [1280] **OVERFLOW** 3 7/8 [98] FACE 1 FACE 2 SHIPPING NO. OF SHIPPING SECTIONS OPERATING HEAVIEST SECTION 51570 lbs+ [23392] kg+ 65010 lbs+ [29488] kg+ 18210 lbs+ [8260] kg+ 3 WEIGHT WEIGHT WEIGHT