

NOTES:

1. (M)- FAN MOTOR LOCATION
2. HEAVIEST SECTION IS UPPER SECTION
3. MPT DENOTES MALE PIPE THREAD
FPT DENOTES FEMALE PIPE THREAD
BFW DENOTES BEVELED FOR WELDING
GVD DENOTES GROOVED
4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS)
5. MAKE-UP WATER PRESSURE
20 psi MIN [137 kPa], 50 psi MAX [344 kPa]
6. 3/4" DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING.
7. *- APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTION PIPING.
8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH IN [METRIC] [mm]

FACE 2 PLAN VIEW

Dimensions for Face 2 Plan View:

- Overall width: 24'-2" [7366]
- Overall height: 24'-2" [7366]
- Top section height: 11'-11" [3632]
- Bottom section height: 11'-11" [3632]
- Section thickness: 4" [102]
- Left side piping: (4) 4 [100] BFW REFRIG IN, (4) 1/2 [15] BFW PURGE
- Right side piping: (4) 4 [100] BFW REFRIG OUT
- Internal dimensions: 9 1/2" * [241], 4 1/8" [105], 53 3/4" * [1365], 18 3/8" * [466], 18'-2 5/8" [5553]

FACE 1 (Top Elevation)

Dimensions for Face 1 (Top Elevation):

- Overall width: 24'-0" [7315]
- Overall height: 122 1/8" [3102]
- Top section height: 96 1/2" [2451]
- Bottom section height: 24'-0" [7315]
- Access door: ACCESS DOOR TYP BOTH SIDES

FACE 1 (Front Elevation)

Dimensions for Face 1 (Front Elevation):

- Overall width: 24'-0" [7315]
- Overall height: 122 1/8" [3102]
- Top section height: 96 1/2" [2451]
- Bottom section height: 24'-0" [7315]
- Access door: ACCESS DOOR TYP BOTH SIDES

SHIPPING WEIGHT	60920 lbs+ [27635] kg+	OPERATING WEIGHT	91180 lbs+ [41360] kg+	HEAVIEST SECTION WEIGHT	20710 lbs+ [9395] kg+	NO. OF SHIPPING SECTIONS	4	DRAWN BY:	TLS
-----------------	------------------------	------------------	------------------------	-------------------------	-----------------------	--------------------------	---	-----------	-----