| NIT  | COOLING TOWER   | <u> </u>  | <b>—————</b>   | EVAPCO, INC. Evapco |                            |   |     | DWG.# ATL4BI24304E5T-DRD-DS      |          | -          |
|--|---|---|--|---------------------|----------------------------|---|-----|----------------------------------|----------|------------|
| IODEL#   | AT 124-4Q30-EV  | SCALE NT  | EVAPO  | CO,                 | INC.                       | evaseu  | S   | ERIAL #                          | DATE:    | 5/19/2024  |
| 2. HEA<br>3. MPT<br>FPT<br>BFW<br>GVD<br>FLG<br>4. +UN<br>ACC<br>5. 3/4"<br>REC<br>6. DIME | FAN MOTOR LOCATION VIEST SECTION IS CASING DENOTES MALE PIPE THE DENOTES FEMALE PIPE T DENOTES GROOVED DENOTES GROOVED DENOTES FLANGE IT WEIGHT DOES NOT INC. ESSORIES (SEE ACCESSO [19mm] DIA. MOUNTING HO OMMENDED STEEL SUPPO ENSIONS LISTED AS FOLLO ENGLISH FT-IN [METRIC] [mm] BOTTOM INLET SPECIFICA DETAIL. | READ<br>HREAD<br>WELDING<br>LUDE<br>DRY DRAWI<br>DLES. REFE<br>DRT DRAWI<br>DWS | 2 5/8" [67]  | OTTOM INL           | BOTTOM OF U                | 18'-2 1/2" [555 FACE B PLAN VIEW  ACCESS DOOF   | R   | FLUID IN  FACE A                 |          | FACE D     |
|  | (2) 2" [50] MPT   | 10<br>11<br>11<br>11'<br>(8" 11'-   | '-11 1/4" [2419]  -2'-1 1/4" [641] -1'-5 3/8" [441] -3 5/8" [92] -1'-0 7/8" -1 3/8" -3070] -1 3/8" -3388] -5 1/8" -5 1/8" -508] 10 3/4" 626] | ON DETAIL           |                            | 7'-0" [213<br>6'-0 1/8" [183<br>31'-9 1/2" [9690]<br>8'-7 1/8" [261<br>10'-2 1/4" [310<br>FLUID OUT | 32] | 3" [80] 13'-4 3/8" [4074] [9201] | -        | 3/8" [924] |
| SHIPPING<br>WEIGHT   | 67840 lbs+ [30775] k  | g+  | OPERATING 94370 lbs+ [42810 WEIGHT   | ] kg+               | HEAVIEST SECTION<br>WEIGHT | 12320 lbs+ [5590] kg+   |     | NO. OF SHIPPING SECTIONS 7       | RAWN BY: | JLG        |