EVAPCO, INC. UNIT MODEL # SERIAL # N.T.S. CQTM3608-DRA-ST **EVAPORATIVE CONDENSER** PMCQ-1034 5/21/2024 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HÉAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 4. +UNIT WEIGHT DOES NOT INCLUDE 9'-9 3/4" ACCESSORIES (SEE ACCESSORY DRAWINGS) [2991] 5. 3/4" DIA. MOUNTING HOLES. REFER TO FACE 1 RECOMMENDED STEEL SUPPORT DRAWING. **PLAN VIEW** 6. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 7. *-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING 36'-2" [11024] **PIPING** 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH IN FACE 2 [METRIC] [mm] 30 3/8* - [772] 57* [1448] (4) 4[100] BFW -REFRIG IN 30 3/4* [781] (4) 4[100] BFW **REFRIG OUT** 69 1/2 [1766] 2[50] MPT MAKE UP **OVERSIZED ACCESS DOORS** 14'-3 7/8" [4366] 119* 3[80] MPT 102 3/8 [2600] [3023] DRAIN 5 3/8 137] 29 [737] 20 5/8 [524] 36'-2" [11024] 23 5/8 [600] 50 3/8 (2) 3[80] FPT 20 [1280] [507]**OVERFLOW** 3 7/8 [98] FACE 1 FACE 2 SHIPPING NO. OF SHIPPING SECTIONS OPERATING HEAVIEST SECTION 45670 lbs+ [20716] kg+ 58870 lbs+ [26703] kg+ 15260 lbs+ [6922] kg+ 3 WEIGHT WEIGHT WEIGHT