EVAPCO, INC. UNIT MODEL # DWG. # DATE SERIAL # **CLOSED CIRCUIT COOLER** ATWB 10-3I12 NTS WZ09182406-MRA-RS 5/13/2024 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS LOWER SECTION **BOTTOM** 3. MPT DENOTES MALE PIPE THREAD OUTLET (M) (M) FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 460 2286 4. **+**UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE SEPARATE DRAWINGS FOR ACCESSORIES) 5. 19mm DIA. MOUNTING HOLES. REFER TO 2578 RECOMMENDED STEEL SUPPORT 6. THE SPRAY PUMP SHOULD BE SIZED FOR 65 L/S AND 34 kPa AT THE INLET CONNECTION FACE 2 7. * - APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING 5486 FACE 1 **PLAN VIEW** 502 -ACCESS DOOR ACCESS DOOR -- 1289 -2229 150 FPT **INLET** 4308 15 FPT 3089 100 BFW **VENT** FLUID OUT 2080 100 BFW 495 FLUID IN 511 860 2578 FACE 2 F#46F61 NO. OF SHIPPING SECTIONS **SHIPPING** OPERATING HEAVIEST SECTION 6690 kq 8870 kg 4320 kq 2 WEIGHT WEIGHT WEIGHT